




RX1330RHP

Thermal Receipt Printer



★ FEATURES

- 58mm/ 80mm/ 82.5mm paper width available.
- IAP function supports firmware update within 5S. Make printer maintained easily.
- Reliable cutter with intelligent code to prevent cutter from cutter jammed.
- Metallic frame mechanism.



RX1330RHP

Thermal Receipt Printer



SPECIFICATION

Printing method	Direct thermal
Printing speed	300mm/s
Paper width	82.5 mm 80mm/58mm
Print width	72 mm (adjustable by commands)
Maximun paper diameter	Φ 83mm
Paper thickness	0.06-0.08mm
Column capacity	576 dots/line 512/line (adjustable by commands)
Line space	3.75mm (Changeable by commands)
Commands	Compatible with ESC/POS
Interface type	USB + Lan/USB + Serial/USB + Serial + WIFI (Option)/USB + serial + Bluetooth(option)
Character size	ANK, Font A: 12x24dots Font B: 9 x 17 dots Simplified/traditional Chinese: 24x24 dots
Dimension	133 x 126 x 130mm (D x W xH)
Gross weight	1.2kg
Bar code	UPC-A/ UPC-E/ JAN(EAN13)/ JAN8 (EAN8)/ CODE39/ ITF/ CODABAR/ CODE93/ CODE128
2-dimension code	QR CODE / PDF417
Code page	PC347 (Standard Europe). Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canadian-French), PC865 (Nordic), WesEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2), PC852 (Latin2), PC858, Iranll, Latvian, Arabic, PT151 (1251)
Cutter	Partial
Cutter life	2 million cuts
Print head life	150 KM
Input buffer	2048 Kbytes
NV Flash	256 Kbytes
Power adaptor	AC110V/220V,50~60Hz
Power source	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Work environment	Temperature: 0~45°C, humidity: 10~80RH%
Storage environment	Temperature: -10~60°C, humidity: 10~90RH%
Operating system	Win XP/ Win Vista/ Win 7/ Win 8/ Win 8.1/ Win 10/ Linux